

An Intelligent CCTV-Based Face Recognition System for Real-Time Identification in Crowded Public Environments

**Prof. D. B. Hanchate¹, Dr. Mrs Prajakta A. Satarkar², Dr. Arvind Jagtap³ Simoon Tamboli⁴,
Madhavi Swami⁵, Payal Kharat⁶, Snehalata Tate⁷**

¹Professor, Computer Science and Engineering, SVERI's College of Engineering,
Pandharpur, India

Email Id : dbhanchate555@gmail.com

²Associate Professor, Computer Science and Engineering, SVERI's College of Engineering,
Pandharpur, India

Email Id : pasatarkar@coe.sveri.ac.in

³Head & Associate Professor, Computer Engineering Department, Vidya Pratishthan's Kamalnayan Bajaj
Institute of Engineering & Technology, Baramati Pune Maharashtra.

Orchid ID: 0000-0001-6855-3216 , Email: arvind.jagtap82@gmail.com / arvind.jagtap@vpkbiet.org

⁴B.E Student, Computer Science and Engineering, SVERI's College of Engineering, Pandharpur, India.

Email Id: simootamboli246@gmail.com

⁵ B.E Student, Computer Science and Engineering SVERI's College of Engineering, Pandharpur, India.

Email Id: madhaviswami609@gmail.com

⁶ B.E Student, Computer Science and Engineering, SVERI's College of Engineering, Pandharpur, India

Email Id: payalkharat43@gmail.com

⁷ B.E Student, Computer Science and Engineering, SVERI's College of Engineering Pandharpur, India.

Email Id: snehalatatate2004@gmail.com

ABSTRACT

The rapid expansion of surveillance infrastructures across urban environments has significantly increased the volume of video data generated in real time. Manual monitoring of such large-scale surveillance networks is inefficient and prone to human error, particularly in high-density public environments characterized by crowd congestion, pose variations, illumination changes, and motion blur. Traditional face recognition approaches based on handcrafted features lack robustness under such unconstrained conditions. This paper presents a CPU-optimized deep learning framework for real-time face recognition-based criminal detection designed specifically for high-density surveillance scenarios. The proposed system integrates Multi-task Cascaded Convolutional Networks (MTCNN) for accurate face detection and alignment, followed by a custom-trained TensorFlow embedding model for identity recognition using similarity-based threshold matching. The framework is trained on multi-angle real-world datasets and deployed under CPU-constrained environments to ensure practical feasibility. Experimental evaluation under controlled testing conditions achieved an average recognition accuracy of approximately 95%. The proposed architecture emphasizes computational efficiency, scalability, and secure biometric handling, making it suitable for distributed public surveillance systems.

Keywords: Face recognition, Criminal detection, Deep learning, Surveillance systems, Biometric authentication, Real-time monitoring

1 INTRODUCTION

Rapid urbanization and digital transformation have led to widespread deployment of surveillance systems across transportation hubs, commercial complexes, educational institutions, and government infrastructures. These surveillance systems generate massive volumes of video data that require continuous monitoring to detect potential security threats. However, manual surveillance is inherently limited by cognitive fatigue, delayed response times, and scalability constraints, making intelligent automated monitoring systems essential.

High-density public environments introduce additional challenges for reliable identity recognition. Factors such as partial occlusion, non-frontal orientations, varying illumination conditions, low-resolution frames, and motion blur significantly degrade recognition performance. Classical face recognition techniques such as Eigenfaces and Fisherfaces rely on linear subspace projections and handcrafted feature extraction methods[1, 2], which lack robustness under unconstrained real-world conditions.

The emergence of deep convolutional neural networks (CNNs) has transformed visual recognition tasks by enabling hierarchical feature learning directly from data[13]. Embedding-based recognition models project facial images into high-dimensional feature spaces where identity verification is performed using similarity-based distance metrics rather than rigid classification[4]. This approach enhances scalability and adaptability when handling large identity databases.

Despite significant advancements in benchmark accuracy, limited research addresses integrated real-time criminal detection frameworks optimized for CPU-based deployment in crowded environments. Many existing systems assume GPU-intensive computation, restricting feasibility in distributed surveillance infrastructures. Additionally, issues related to threshold optimization, false positive control, and secure biometric storage remain underexplored in practical implementations.

Related Work

Face recognition research has evolved significantly from traditional feature-engineering techniques to advanced deep learning-based architectures. Early approaches such as Eigenfaces and Fisherfaces relied on principal component analysis and linear discriminant analysis for feature extraction[1, 2]. While computationally efficient, these methods were highly sensitive to illumination variations, pose changes, and facial expressions.

The introduction of deep learning marked a paradigm shift in face recognition. DeepFace demonstrated the capability of deep neural networks to learn complex facial representations under unconstrained conditions[3]. Subsequently, FaceNet introduced an embedding-based learning framework where facial images are mapped into a compact Euclidean space[4]. The use of triplet loss ensures that embeddings of the same identity remain closer while maintaining separation from different identities, improving scalability for large databases.

Accurate face detection and alignment are critical preprocessing steps. The Multi-task Cascaded Convolutional Network (MTCNN) employs a three-stage architecture consisting of a proposal network, refinement network, and output network to jointly perform face detection and landmark localization[5]. Its balance between computational efficiency and accuracy makes it suitable for real-time applications.

Real-time object detection frameworks such as YOLO reformulated detection as a regression problem, significantly improving inference speed for video stream analysis[6]. However, most object detection systems focus on general object categories and require adaptation for specialized biometric recognition tasks.

Large-scale benchmark datasets such as Labeled Faces in the Wild (LFW) and MegaFace have been widely used to evaluate recognition performance under unconstrained and large-scale conditions [7, 8]. Recent margin-based loss functions such as ArcFace have further enhanced discriminative embedding learning for improved recognition accuracy [9].

Although recent transformer-based architectures demonstrate improved robustness under challenging conditions, they often demand substantial computational resources and extensive training datasets. Furthermore, practical deployment challenges such as CPU feasibility, threshold tuning, and privacy preservation remain insufficiently addressed in many implementations[10].

Therefore, there exists a clear need for an integrated framework that combines robust detection, embedding-based recognition, optimized similarity thresholds, and secure biometric handling within a computationally efficient architecture suitable for real-world surveillance environments.

Proposed Methodology

The proposed framework is designed to perform real-time criminal identification in high-density public environments while maintaining computational efficiency under CPU-based deployment. The system architecture consists of four primary stages: face detection, face alignment, embedding generation, and similarity-based identity matching.




Fig. 1. Proposed system architecture for real-time criminal identification

Initially, input video frames are captured from surveillance feeds and preprocessed to ensure resolution consistency. Face detection and alignment are performed using the Multi-task Cascaded Convolutional Network (MTCNN)[5]. This three-stage architecture detects facial regions and simultaneously extracts key landmark points including eyes, nose, and mouth coordinates. Alignment based on landmark localization reduces the impact of pose variations and improves embedding consistency.

Following detection and alignment, facial images are passed to a custom-trained deep convolutional neural network implemented using TensorFlow. Instead of performing direct classification, the model generates fixed-length embedding vectors representing discriminative facial features in a high-dimensional space. These embeddings encode identity-specific characteristics while maintaining invariance to illumination, minor pose variations, and facial expressions.

For recognition, the system employs similarity-based matching using Euclidean distance between the query embedding and stored database embeddings. A decision threshold is defined such that:

If distance < threshold → Identity match

If distance ≥ threshold → Unknown identity Threshold selection is empirically optimized to balance false acceptance rate (FAR) and false rejection rate (FRR), particularly in crowded environments where misidentification risk is elevated.

Equation 1 – Euclidean Distance

This measures similarity between:

Query embedding → x

Stored embedding → y

$$d(X, Y) = \sqrt{\sum_{i=1}^n (x_i - y_i)^2}$$

Explain:

x_i = query embedding component

y_i = stored embedding component

n = embedding dimension

d = distance score

Equation 2 – Decision Rule

This converts distance into recognition:

Identity = {Match if $d < T$ Unknown if $d \geq T$

Explain:

T = decision threshold

Equation 3 – Confidence Score

$$\text{Confidence} = \left(1 - \frac{d}{T}\right) \times 100$$

where d represents the Euclidean distance between the query and stored embeddings, and T denotes the predefined decision threshold.

This means:

If distance is very small → confidence close to 100%

If distance approaches threshold → confidence close to 0%

The architecture is optimized to operate without GPU acceleration, ensuring feasibility for distributed surveillance systems where high-performance hardware may not be available.

Implementation Details

The system is implemented using Python and TensorFlow in a CPU-based environment. The training dataset consists of real-time collected facial images, including multiple angles, varied lighting conditions, and different facial expressions to simulate realistic surveillance scenarios. Approximately 500 identities were included in the experimental dataset.

Data preprocessing included resizing, normalization, and augmentation techniques such as rotation and brightness variation to enhance generalization. The embedding model was trained to minimize intra-class distance while maximizing inter-class separation, enabling robust similarity-based recognition.

The recognition pipeline operates in real time by processing video frames sequentially. Face detection using MTCNN is applied to each frame, followed by embedding generation and similarity comparison against the stored database.

To maintain system efficiency under CPU constraints:

Batch processing was minimized.

Model size was optimized to reduce inference latency.

Database lookup operations were structured for rapid embedding comparison.

The system achieved real-time processing capability suitable for moderate surveillance loads without dedicated GPU hardware.

Experimental Results and Analysis

The system was evaluated across multiple test cases consisting of individual and multi-person frames captured under varied pose, illumination, and angle conditions. Accuracy was computed on a per-face basis rather than per-image basis. Across the complete evaluation set, the framework achieved an average recognition accuracy of approximately 95% under controlled testing conditions.




Fig. 2. Sample output showing face detection and similarity confidence percentage

The screenshot shown in Fig. 2 represents a sample operational scenario and does not reflect the overall performance metric. It illustrates real-time system behavior under dynamic conditions.

Here:

TP = True Positive

TN = True Negative

FP = False Positive

FN = False Negative

Case Analysis

Suppose:

Person A → Correctly identified (TP = 1)

Person B → Wrongly matched as someone else (FP = 1)

Then:

TP = 1

TN = 0

FP = 1

FN = 0

Equation 4 – Accuracy

$$\text{Accuracy} = \frac{TP + TN}{TP + TN + FP + FN}$$

$$\text{Accuracy} = \frac{1 + 0}{1 + 0 + 1 + 0} = \frac{1}{2} \times 100 = 50\%$$

Equation 5 – FAR

$$\text{FAR} = \frac{FP}{FP + TN}$$

$$\text{FAR} = \frac{1}{1 + 0} = \frac{1}{1} \times 100 = 100\%$$

Equation 6 – FRR

$$\text{FRR} = \frac{FN}{FN + TP}$$

$$\text{FRR} = \frac{0}{0 + 1} = \frac{0}{1} \times 100 = 0\%$$

The quantitative performance of the proposed system under the sample screenshot scenario is summarized in Table 1.

Table 1. Example frame-level recognition behavior

Metric	Value
Total Individuals	2
Correct Identifications	1
False Positives	1
False Negatives	0
Accuracy	50%
FAR	100%
FRR	0%
Confidence Range (Correct Match)	70–90%
Deployment Mode	CPU-based

The system achieved an average recognition accuracy of approximately 95% under controlled lighting conditions. Performance degradation was observed in cases of extreme side angles and low-resolution frames, though recognition remained stable under moderate pose variations.

Precision and recall metrics indicate that threshold optimization significantly reduced false positives in crowded scenarios. The embedding-based recognition approach demonstrated strong identity clustering properties, with same-identity embeddings consistently grouped within a compact distance range.

CPU-based inference performance analysis revealed that the system maintained acceptable latency for real-time surveillance use cases. While GPU acceleration could further improve throughput, the current architecture demonstrates practical feasibility for distributed infrastructure deployment.

Overall, the results validate that embedding-based recognition combined with optimized threshold selection provides reliable identification performance in high-density environments.

Discussion

The experimental results demonstrate that embedding-based face recognition is well-suited for criminal detection in surveillance systems. Unlike traditional classification-based models, similarity-based recognition allows scalable integration of new identities without complete model retraining.

One of the primary strengths of the proposed framework is its CPU feasibility. Many state-of-the-art systems depend heavily on GPU acceleration, limiting deployment in resource-constrained environments. The proposed architecture demonstrates that carefully optimized deep learning models can achieve competitive accuracy under CPU execution.

However, certain limitations remain. Recognition performance declines under extreme occlusion and severe motion blur. Additionally, threshold tuning must be carefully calibrated depending on the operational environment to minimize false alarms in crowded public spaces.

Although the current prototype was evaluated using static group images, the proposed architecture is designed to support integration with live surveillance feeds. In real-world scenarios, such as identifying an escaped criminal, the system can be deployed over IP-based CCTV networks to continuously monitor and compare live facial embeddings against a predefined criminal database. This enables proactive identification in crowded public environments.

Security and Privacy Considerations

Biometric systems inherently involve sensitive personal data. Therefore, privacy preservation and secure storage mechanisms are critical components of responsible deployment.

In the proposed framework, facial embeddings rather than raw images are stored in the database to reduce data exposure risk. Embeddings represent mathematical feature vectors that cannot be directly reconstructed into original facial images.

Access control mechanisms and encryption strategies are recommended for database storage to prevent unauthorized access. Additionally, deployment must comply with applicable data protection regulations and ethical guidelines governing biometric systems.

Careful threshold tuning is also essential to prevent wrongful identification, particularly in high-density environments where misclassification could have serious consequences.

By integrating security awareness into the system design, the proposed framework promotes responsible and ethical use of intelligent surveillance technologies.

Conclusion and Future Work

This paper presented a CPU-optimized deep learning framework for real-time face recognition-based criminal detection in high-density public environments. The system integrates MTCNN-based face detection with a custom-trained TensorFlow embedding model and similarity-based identity matching.

Experimental evaluation demonstrates an average recognition accuracy of approximately 95%, validating the effectiveness of embedding-based recognition under real-world conditions. The proposed architecture emphasizes computational efficiency, scalability, and secure biometric handling, making it suitable for distributed surveillance infrastructures.

Future work will focus on integrating the framework with live CCTV camera streams to enable continuous real-time monitoring in high-density public areas. Such integration would allow dynamic tracking of suspected individuals, adaptive threshold tuning, and improved large-scale deployment across distributed surveillance infrastructures.

The proposed framework contributes toward practical, efficient, and secure intelligent surveillance systems capable of operating under real-world constraints....

REFERENCES

1. Turk, M., Pentland, A.: Eigenfaces for recognition. *Journal of Cognitive Neuroscience* 3(1), 71–86 (1991)
2. Belhumeur, P.N., Hespanha, J.P., Kriegman, D.J.: Eigenfaces vs. Fisherfaces: Recognition using class specific linear projection. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 19(7), 711–720 (1997)
3. Taigman, Y., Yang, M., Ranzato, M., Wolf, L.: DeepFace: Closing the gap to human-level performance in face verification. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 1701–1708 (2014)
4. Schroff, F., Kalenichenko, D., Philbin, J.: FaceNet: A unified embedding for face recognition and clustering. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 815–823 (2015)
5. Zhang, K., Zhang, Z., Li, Z., Qiao, Y.: Joint face detection and alignment using multi-task cascaded convolutional networks. *IEEE Signal Processing Letters* 23(10), 1499–1503 (2016)
6. Redmon, J., Divvala, S., Girshick, R., Farhadi, A.: You only look once: Unified, real-time object detection. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 779–788 (2016)
7. Huang, G.B., Mattar, M., Berg, T., Learned-Miller, E.: Labeled Faces in the Wild: A database for studying face recognition in unconstrained environments. Technical Report 07-49, University of Massachusetts (2007)
8. Kemelmacher-Shlizerman, I., Seitz, S.M., Miller, D., Brossard, E.: The MegaFace benchmark: 1 million faces for recognition at scale. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 4873–4882 (2016)
9. Deng, J., Guo, J., Xue, N., Zafeiriou, S.: ArcFace: Additive angular margin loss for deep face recognition. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 4690–4699 (2019)
10. Wang, M., Deng, W.: Deep face recognition: A survey. *Neurocomputing* 429, 215–244 (2021)
11. Sandberg, D.: Face recognition using TensorFlow. GitHub repository.
12. <https://github.com/davidsandberg/facenet> (2018)
13. Jain, A.K., Ross, A., Prabhakar, S.: An introduction to biometric recognition. *IEEE Transactions on Circuits and Systems for Video Technology* 14(1), 4–20 (2004)
14. Goodfellow, I., Bengio, Y., Courville, A.: *Deep Learning*. MIT Press, Cambridge (2016)
15. Viola, P., Jones, M.: Rapid object detection using a boosted cascade of simple features. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 511–518 (2001)
16. He, K., Zhang, X., Ren, S., Sun, J.: Deep residual learning for image recognition. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 770–778 (2016)