CINEFORUM
ISSN: 0009-7039
Vol. 66. No. S5, 2026 (Special Issue S5)

AI-Driven Adaptive Robotic Manufacturing with Deep Reinforcement Learning for Market-Responsive Production

Dr. Geeta N. Brijwani[1], Dr. Pragati V. Thawani[2]

[1]Department of Computer Science, K.C. College, HSNC University, Mumbai, India
[2]Department of Information Technology, K.C. College, HSNC University, Mumbai, India

ABSTRACT

The emergence of Industry 4.0 has transformed manufacturing from conventional automated production towards intelligent, connected and adaptive production systems. However, many robotic manufacturing systems continue to depend on predefined programs and fixed production schedules, making them less responsive to sudden changes in market demand, machine conditions, inventory levels and production priorities. This research proposes a **Market-Responsive Robotic Automation Framework** integrating Artificial Intelligence (AI), Deep Learning (DL), Internet of Things (IoT), and Deep Reinforcement Learning (DRL) for adaptive manufacturing.

The proposed framework combines market and enterprise resource planning (ERP) information with real-time shop-floor data. Deep Learning models such as Long Short-Term Memory (LSTM), Gated Recurrent Unit (GRU), and Temporal Convolutional Networks (TCN) can be employed for demand forecasting. The predicted demand is integrated with machine condition, inventory, production queue, energy and quality information to construct the state of the manufacturing environment. A DRL agent subsequently determines adaptive actions including production scheduling, batch switching, machine allocation, production-speed adjustment and robotic parameter selection. A reward mechanism evaluates throughput, downtime, quality, energy consumption and demand fulfilment, enabling continuous improvement.

The research further proposes a simulation-oriented evaluation framework for comparing fixed rule-based scheduling, Genetic Algorithm (GA), Deep Q-Network (DQN), and a proposed demand-aware DRL approach. Illustrative results indicate the potential of demand-aware reinforcement learning to improve throughput and demand fulfilment while reducing downtime and energy-related penalties. However, the numerical values presented are illustrative and should be replaced with experimentally validated results before journal submission. The proposed framework provides a foundation for developing flexible, intelligent and market-responsive manufacturing systems suitable for Indian Industry 4.0 environments.

Keywords: Artificial Intelligence, Deep Learning, Deep Reinforcement Learning, Robotic Automation, Industry 4.0, Smart Manufacturing, IoT, Demand Forecasting, Dynamic Scheduling, Adaptive Manufacturing.

1. INTRODUCTION

Manufacturing industries are increasingly adopting intelligent technologies to improve productivity, flexibility, quality and competitiveness. The Industry 4.0 paradigm has introduced interconnected machines, industrial robots, cyber-physical systems, Internet of Things, cloud computing, Artificial Intelligence and advanced analytics into production environments.[1]

Robotic automation has traditionally been associated with repetitive and predefined operations. Industrial robots can perform manufacturing activities with high precision and consistency, but conventional robotic systems generally execute predefined instructions. When production requirements change significantly, operators may need to modify schedules or reprogram machines.

This limitation becomes important in modern manufacturing environments where customer requirements and market demand may change rapidly. Production systems must respond to product variation, changing order quantities, machine failures, raw-material availability and delivery requirements.

The research report forming the basis of this study identifies the need for self-adaptive robotic software capable of responding to market fluctuations in Indian manufacturing. It proposes the integration of Artificial Intelligence, Deep Learning, IoT and Reinforcement Learning to improve production flexibility and operational efficiency.

Deep Reinforcement Learning is particularly suitable for dynamic manufacturing decision-making because it enables an agent to learn actions from interaction with an environment. Recent research has demonstrated increasing interest in DRL for dynamic job-shop scheduling, production planning and manufacturing optimization. These studies also identify challenges involving scalability, interpretability, robustness, data availability and real-world deployment.

OPEN ACCESS © CINEFORUM

This research therefore proposes a framework in which market demand is not treated as an isolated forecasting problem. Instead, demand forecasting becomes an input to the production decision-making system. Market information, machine condition and production status are jointly considered by the intelligent controller.[2,3]
The fundamental concept is:
Market Intelligence + Shop-Floor Intelligence + Reinforcement Learning = Market-Responsive Manufacturing

2. RESEARCH PROBLEM

Conventional manufacturing systems commonly use predefined production schedules and rule-based robotic control. Such systems are effective when demand and production conditions remain relatively stable. However, their flexibility decreases when the manufacturing environment becomes dynamic.[2,4]
The major research problems are:
Limited responsiveness to sudden changes in market demand.
Dependence on manually prepared production schedules.
Manual reconfiguration of robotic production processes.
Limited integration of market forecasts with shop-floor decisions.
Fragmented use of machine and sensor information.
Difficulty in simultaneously optimizing productivity, quality, energy and delivery.
Limited continuous learning from production outcomes.
Challenges associated with deploying AI-based systems in heterogeneous Indian manufacturing environments.
The proposed research addresses these issues through an integrated AI-IoT-DL-DRL architecture.

3. RESEARCH OBJECTIVES

The objectives of this research are:
To develop a market-responsive robotic automation framework for adaptive manufacturing.
To integrate market and ERP information with manufacturing data.
To apply Deep Learning for manufacturing demand forecasting.
To integrate IoT-based real-time machine monitoring.
To develop a DRL-based dynamic production scheduling mechanism.
To enable adaptive robotic production decisions.
To optimize throughput, downtime, quality, energy and demand fulfilment.
To establish a continuous feedback mechanism for learning.
To compare the proposed approach with conventional scheduling techniques.
To investigate the applicability of the framework to Indian manufacturing.
These objectives correspond closely with the source research report's objectives concerning adaptive algorithms, validation, cost-benefit analysis, Industry 4.0, competitiveness and sustainability.[5]

4. RELATED WORK

4.1 Artificial Intelligence in Manufacturing

AI is increasingly used for predictive maintenance, demand forecasting, quality inspection, anomaly detection, scheduling and process optimization. Machine learning models can identify patterns in production and market data and provide predictive information for decision-making.
AI-enabled smart automation has also been investigated in the context of Indian manufacturing and Industry 4.0.[6,7,8]

4.2 Deep Learning for Demand Forecasting

Demand forecasting is an important component of market-responsive manufacturing. Traditional forecasting approaches may have difficulty representing nonlinear and complex relationships in demand data.
Deep Learning models can learn temporal patterns from historical demand.
For this research, candidate models include:
LSTM
GRU
TCN
Transformer-based time-series models
The source research specifically proposes LSTM/GRU/TCN-based demand forecasting as part of the adaptive manufacturing architecture.

OPEN ACCESS © CINEFORUM

4.3 Reinforcement Learning for Manufacturing

Reinforcement Learning formulates decision-making as interaction between an agent and an environment.
In manufacturing:
Agent: Intelligent scheduling controller
Environment: Manufacturing system
State: Current production condition
Action: Production/scheduling decision
Reward: Performance feedback
The agent learns a policy that maximizes cumulative reward.
Recent reviews report growing applications of DRL to job-shop and production scheduling, including dynamic environments with equipment failures and changing job requirements. [9]

4.4 Research Gap

Existing studies provide strong evidence for AI-based manufacturing optimization, but there remains a need for integrated architectures that connect:
Demand Forecasting → Production Scheduling → Machine Condition → Robotic Action → Performance Feedback
The proposed research addresses this integration gap. [11]

5. PROPOSED SYSTEM ARCHITECTURE

The proposed framework consists of seven major components:
Market and ERP data acquisition
Deep Learning demand forecasting
IoT shop-floor monitoring
Manufacturing-state construction
Deep Reinforcement Learning
Human supervisory interface
Robotic and production execution




Figure 1. Proposed Market-Responsive Robotic Automation Architecture

OPEN ACCESS © CINEFORUM

The source report similarly proposes market-data acquisition, LSTM/GRU/TCN forecasting, IoT sensing, AI scheduling, DQN/PPO/A3C-based reinforcement learning and a continuous self-training mechanism.[12]

Data Acquisition Layer
The first layer collects information from both external and internal sources.
Market data
Historical sales
Customer orders
Market trends
Seasonal demand
Product popularity
Future orders
ERP data
Inventory
Production orders
Raw-material availability
Delivery schedules
Product information
Machine data
Temperature
Vibration
Tool wear
Cycle time
Machine availability
Energy consumption
Quality data
Defect count
Inspection results
Rework
Product quality indicators
This combination provides a comprehensive representation of the manufacturing environment.

Demand Forecasting Model
Let historical demand be represented as:
[D={d_1,d_2,,d_t}]
A forecasting model receives a historical window:
[X_t=[d_{t-k},d_{t-k+1},…,d_t]]
and predicts future demand:
[{t+h}=f(X_t)]
where:
(_{t+h}) = predicted demand
(h) = forecasting horizon
(f_) = trained Deep Learning model
() = model parameters
LSTM, GRU or TCN may be selected based on forecasting performance.
Forecast accuracy can be evaluated using:
Mean Absolute Error
[MAE=_{i=1}^{n}|y_i-|]
Root Mean Square Error
[RMSE=]
Mean Absolute Percentage Error
[MAPE=_{i=1}^{n}||]

IoT-Based Manufacturing Monitoring
IoT sensors provide real-time information from machines and production lines.
The sensor vector can be represented as:

OPEN ACCESS © CINEFORUM

[M_t=[T_t,V_t,W_t,C_t,E_t]]
where:
(T_t) = temperature
(V_t) = vibration
(W_t) = tool-wear condition
(C_t) = cycle time
(E_t) = energy consumption
The sensor information enables the system to identify abnormal machine conditions and incorporate them into scheduling decisions.

Manufacturing State Representation
The manufacturing state is defined as:
[S_t=[,I_t,M_t,Q_t,P_t,E_t]]
where:
() = predicted demand
(I_t) = inventory level
(M_t) = machine condition
(Q_t) = production queue
(P_t) = production priority
(E_t) = energy status
This state representation combines market-level and shop-floor-level information.

Action Space
The DRL agent may select one or more of the following actions:
[A_t={a_1,a_2,…,a_n}]
Possible actions include:
Select next production job
Change production sequence
Change batch size
Allocate job to another machine
Adjust production speed
Switch product
Reschedule production
Modify permissible robotic operating parameters
All robotic actions must remain within predefined safety and operational constraints.

Reward Function
A multi-objective reward function is proposed:
[R_t=w_1T_t-w_2D_t-w_3E_t-w_4Q_t-w_5M_t]
where:
(T_t) = throughput
(D_t) = downtime
(E_t) = energy consumption
(Q_t) = quality/defect penalty
(M_t) = market-demand mismatch
(w_1,w_2,…w_5) = objective weights
The reward function allows the system to balance competing manufacturing objectives.
For example, maximizing production alone may increase energy consumption or defects. The multi-objective reward prevents the system from optimizing only one performance measure.

Deep Reinforcement Learning Model
The manufacturing problem can be formulated as a Markov Decision Process:
[M=(S,A,P,R,)]
where:
(S) = state space
(A) = action space

OPEN ACCESS © CINEFORUM

(P) = transition probability
(R) = reward
() = discount factor
Three candidate DRL algorithms are considered:
DQN-Suitable for discrete action spaces.
PPO-Suitable for stable policy optimization and can be extended to complex production environments.
A3C-Can be used for distributed learning in appropriate environments.
The source report identifies DQN, PPO and A3C as candidate reinforcement-learning algorithms for adaptive robotic manufacturing.

6. PROPOSED METHODOLOGY

The proposed research follows the following sequence:
Step 1: Data Collection
Collect historical market, production, machine and quality data.
Step 2: Data Preprocessing
Handle missing values, noise, outliers and normalization.
Step 3: Demand Forecasting
Train and validate LSTM/GRU/TCN models.
Step 4: IoT Integration
Collect real-time manufacturing information.
Step 5: State Construction
Combine demand forecast, inventory, machine condition and production information.
Step 6: DRL Training
Train the DRL agent in a simulated manufacturing environment.
Step 7: Decision Generation
Generate adaptive production decisions.
Step 8: Performance Evaluation
Measure throughput, downtime, energy, quality and demand fulfilment.
Step 9: Feedback
Return performance information to the learning system.
Step 10: Policy Update
Update the DRL model based on reward.




Figure 2. Proposed Methodology

OPEN ACCESS © CINEFORUM

7. PROPOSED ALGORITHM

Algorithm 1: Market-Responsive Robotic Manufacturing
Input: Market data, ERP data, IoT sensor data, production data
Output: Adaptive production decision
Initialize forecasting model (F).
Initialize DRL agent (A).
Collect historical demand data.
Preprocess the demand dataset.
Train the demand forecasting model.
Collect real-time machine and production information.
Generate future demand prediction.
Construct current state (S_t).
Generate feasible actions (A_t).
Select action using the DRL policy.
Execute the selected production/scheduling action.
Observe production outcome.
Calculate reward (R_t).
Store the state-action-reward transition.
Update the DRL policy.
Repeat until the end of the production horizon.

8. EXPERIMENTAL DESIGN

A simulation-based manufacturing environment is proposed for initial validation.
The environment should contain multiple machines and products and should allow demand and machine conditions to change over time.

Table1: Three major experimental scenarios are proposed.

Scenario	Manufacturing Condition
S1	**Stable demand and normal machine operation**
S2	**Sudden increase/decrease in market demand**
S3	**Demand fluctuation combined with machine failure**

The purpose of Scenario S3 is particularly important because real manufacturing systems may experience simultaneous market and operational disturbances.

9. COMPARATIVE METHODS

The proposed system can be compared against:
Fixed rule-based scheduling
Genetic Algorithm scheduling
DQN-based scheduling
Proposed demand-aware DRL scheduling
The comparison should use identical manufacturing conditions.

10. PERFORMANCE METRICS

OPEN ACCESS © CINEFORUM

Table 2: Performance Metrics

The following metrics are recommended.[13,14]

Metric	Measurement Objective
Throughput	Production output
Makespan	Completion time
Machine utilization	Resource efficiency
Downtime	Operational interruption
Demand fulfilment	Market responsiveness
Energy consumption	Sustainability
Defect rate	Product quality
Production cost	Economic efficiency
Adaptation time	Response speed
Inventory mismatch	Demand-production alignment

11. ILLUSTRATIVE RESULTS

Because actual industrial data and completed experimental runs are not available in the source material, the following values are presented as **illustrative evaluation results only**. They demonstrate the structure and interpretation of the proposed experiment and must not be reported as measured industrial findings.

Table 3. Illustrative Comparative Results

Method	Throughput (units/day)	Downtime (hrs/day)	Demand Fulfilment (%)	Energy Index
Fixed Rule-Based	820	4.8	78	100
GA Scheduling	875	4.2	84	96
DQN	925	3.5	90	91
Proposed PPO Demand Forecast	965	2.8	95	87




Figure 3. Comparison of Manufacturing Throughput

OPEN ACCESS © CINEFORUM




Figure 4. Comparison of Manufacturing Downtime




Figure 4. Comparison of Demand Fulfillment




Figure 5. Comparison of Energy Index

OPEN ACCESS © CINEFORUM

The illustrative values show the expected direction of improvement when market forecasting is integrated with adaptive scheduling. The comparative analysis indicates that the proposed PPO-based demand-aware framework achieves the most favorable performance across the selected manufacturing indicators. It provides the highest throughput and demand fulfilment while exhibiting lower downtime and energy index compared with the baseline approaches. These values are illustrative and are intended to demonstrate the proposed evaluation framework; actual experimental validation is required before treating the results as empirical findings.

12. THROUGHPUT ANALYSIS

In the illustrative comparison, the fixed rule-based method achieves 820 units/day, whereas the proposed demand-aware approach achieves 965 units/day.
The percentage increase relative to the fixed approach is:
[=17.68%]
Thus, the illustrative model demonstrates a potential **17.68% increase in throughput**.
This value is not an experimentally established improvement; it is derived from the illustrative values used for demonstrating the evaluation methodology.

Downtime Analysis

The illustrative downtime decreases from 4.8 hours/day for the fixed rule-based approach to 2.8 hours/day for the proposed approach.
The corresponding illustrative reduction is:
[=41.67%]
This indicates how machine-condition information and adaptive scheduling could potentially reduce unnecessary machine idle time.
Again, this percentage represents the illustrative dataset rather than an actual industrial result.

Demand-Fulfilment Analysis

Demand fulfilment increases from 78% in the fixed scheduling system to 95% in the proposed approach in the illustrative evaluation.
[=21.79%]
The improvement illustrates the principal advantage of connecting demand forecasting to production scheduling. A conventional system may respond only after an order increase occurs, whereas the proposed architecture can use predicted demand as an input to production planning.

Energy Analysis

The illustrative energy index decreases from 100 for the fixed approach to 87 for the proposed approach.
[=13%]
The proposed reward function can discourage unnecessary machine operation and inefficient production decisions.
However, actual energy savings must be determined experimentally using machine-level energy measurements.

13. DISCUSSION

The proposed framework differs from conventional robotic automation because it introduces an intelligent decision layer between manufacturing information and production execution.
In a conventional system, a sudden demand increase may require:
Demand Change → Human Analysis → Schedule Modification → Robot Reprogramming → Production
The proposed framework aims to reduce this response chain to:
Demand Data → AI Forecast → DRL Decision → Controlled Production Adaptation
The integration of machine-condition data adds another dimension.
For example, assume that demand for Product B is predicted to increase. The DRL agent may increase the production priority of Product B. However, if the machine required for Product B simultaneously reports abnormal vibration, the agent can consider an alternative machine or production sequence.[15,16]
Thus, the decision is based on:
[+ + + + +]
This integrated decision-making process is the central contribution of the proposed framework.
Recent reviews of DRL-based manufacturing scheduling similarly emphasize dynamic adaptation, multi-objective optimization and the ability to respond to changing manufacturing conditions.

14. HUMAN-IN-THE-LOOP MANUFACTURING

Complete autonomy is not always desirable in industrial environments.

OPEN ACCESS © CINEFORUM

The proposed system therefore includes a human supervisory layer.[17,18]
The supervisor can:
Monitor AI decisions
Approve critical actions
Override unsafe decisions
Adjust objective weights
Define production constraints
Review performance
Provide domain knowledge
This approach combines computational intelligence with human manufacturing expertise.

15. SAFETY AND SECURITY

AI-controlled robotic systems must operate within strict constraints.[19]
The proposed framework should include:
Maximum/minimum operating limits
Emergency-stop mechanisms
Safe robotic operating ranges
Human authorization for critical changes
Network security
Access control
Data encryption
Audit logs
Model monitoring
IoT-connected manufacturing systems also require cybersecurity because machine and production data may become accessible through interconnected networks.

16. APPLICABILITY TO INDIAN MANUFACTURING

The proposed framework is particularly relevant to Indian manufacturing because manufacturing organizations vary considerably in scale, automation level and technological maturity.[20]
Potential application sectors include:
Automotive
Electronics
Textile
Packaging
Pharmaceutical
Consumer goods
Assembly
Engineering manufacturing
The source report proposes compatibility with industrial robotic environments including ABB, KUKA and FANUC systems, while also considering integration with legacy machines and edge/cloud deployment.
For SMEs, a phased implementation may be preferable because complete replacement of existing machinery may be economically impractical.

17. PROPOSED IMPLEMENTATION ROADMAP

Phase 1: Data Preparation
Establish market, ERP, production and sensor databases.
Phase 2: Forecasting
Develop and validate the demand prediction model.
Phase 3: Digital Simulation
Construct a virtual manufacturing environment.
Phase 4: DRL Training
Train the scheduling agent.
Phase 5: Offline Testing
Compare AI decisions with existing production schedules.
Phase 6: Human-in-the-Loop Pilot
Allow supervisors to validate AI decisions.

OPEN ACCESS © CINEFORUM

Phase 7: Controlled Deployment
Introduce the framework to a selected manufacturing cell.
Phase 8: Continuous Learning
Monitor performance and periodically update the models.



Figure 6. Proposed Implementation Roadmap.

18. LIMITATIONS

The proposed research has several limitations.
First, the framework requires reliable market and manufacturing data. Poor-quality or incomplete data may reduce forecasting and decision-making performance.
Second, DRL models can require significant computational resources during training.
Third, a model trained in a simulated environment may not perform identically in a real factory.
Fourth, robotic safety constraints must always take priority over AI optimization.
Fifth, the proposed framework requires integration with existing ERP, IoT, PLC and robotic systems, which may be difficult in heterogeneous legacy environments.
Finally, the numerical results presented in this paper are illustrative because the source research does not provide completed experimental measurements. Therefore, they should be replaced with reproducible experimental results before submitting the paper as an empirical research article.

19. FUTURE SCOPE

Future research can extend the proposed framework in several directions.

19.1 Digital Twins

Digital twins can be used to simulate production decisions before implementation.

OPEN ACCESS © CINEFORUM

19.2 Multi-Agent Reinforcement Learning
Multiple robots and machines can be represented as interacting agents.

19.3 Explainable AI
Explainability can help production managers understand why a particular scheduling decision was selected.

19.4 Transformer-Based Forecasting
Transformer architectures can be investigated for complex demand time series.

19.5 Edge AI
Deploying models at the edge can reduce communication latency.

19.6 Generative AI
Generative AI can provide natural-language explanations and operator assistance.

19.7 Sustainable Manufacturing
Future reward functions can incorporate carbon emissions, material waste and renewable-energy availability.

19.8 Real-World Industrial Validation
The most important future research direction is validation using actual Indian manufacturing data and production environments.

20. CONCLUSION
This research presented a Market-Responsive Robotic Automation Framework integrating Artificial Intelligence, Deep Learning, IoT and Deep Reinforcement Learning for adaptive manufacturing.
The proposed framework addresses an important limitation of conventional robotic automation: dependence on predefined schedules and manual adaptation. By incorporating market-demand forecasting into the manufacturing decision process, the system can potentially respond to changing customer requirements before those changes cause major production disruptions.
The architecture integrates market information, ERP data, Deep Learning forecasting, IoT-based machine monitoring, DRL-based scheduling and robotic execution. The DRL agent considers demand prediction, inventory, machine condition, production queues, quality and energy information while selecting production actions.
An illustrative comparative evaluation demonstrates how the proposed approach can be assessed against fixed scheduling, GA and DQN approaches using throughput, downtime, demand fulfilment and energy consumption. The illustrative values suggest the potential advantages of demand-aware DRL; however, they are not claimed as actual industrial measurements.
The major research contribution is therefore the proposed integration of:
Market Forecasting + IoT Monitoring + Deep Reinforcement Learning + Robotic Automation
This framework can provide a foundation for future development of flexible and intelligent manufacturing systems in India. Further experimental validation using real-world datasets, simulation environments and industrial robotic systems is required to establish its quantitative effectiveness

REFERENCES
1. G. Biau and E. Scornet, “A random forest guided tour,” TEST, vol. 25, no. 2, pp. 197–227, 2016, doi:
2. 10.1007/s11749-016-0481-7.
3. I. Goodfellow, Y. Bengio, and A. Courville, Deep Learning. Cambridge, MA, USA: MIT Press, 2016.
4. Y. LeCun, Y. Bengio, and G. Hinton, “Deep learning,” Nature, vol. 521, no. 7553, pp. 436–444, 2015, doi: 10.1038/nature14539.
5. R. S. Sutton and A. G. Barto, Reinforcement Learning: An Introduction, 2nd ed. Cambridge, MA, USA:
6. MIT Press, 2018.
7. J. Schmidhuber, “Deep learning in neural networks: An overview,” Neural Networks, vol. 61, pp. 85–
8. 117, 2015, doi: 10.1016/j.neunet.2014.09.003.
9. M. Chui, J. Manyika, and M. Miremadi, “Where machines could replace humans—and where they can’t (yet),” McKinsey Quarterly, 2016.

OPEN ACCESS © CINEFORUM

10. P. Pandit and Y. Zhu, “An overview of security in deep learning,” arXiv preprint arXiv:1611.07298,
11. 2016.
12. S. Thrun and L. Pratt, Eds., Learning to Learn. Boston, MA, USA: Springer, 2012.
13. A. Y. Ng, Machine Learning Yearning: Technical Strategy for AI Engineers, in the Era of Deep Learning. DeepLearning.AI, 2018.
14. J. D. Kelleher, B. M. Namee, and A. D’Arcy, Fundamentals of Machine Learning for Predictive Data Analytics: Algorithms, Worked Examples, and Case Studies. Cambridge, MA, USA: MIT Press, 2015.
15. Y. Lu, X. Xu, and J. Xu, “Development of a hybrid manufacturing cloud,” Journal of Manufacturing Systems, vol. 33, no. 4, pp. 551–566, 2014, doi: 10.1016/j.jmsy.2014.05.003.
16. S. Mittal, M. A. Khan, D. Romero, and T. Wuest, “A critical review of smart manufacturing & Industry 4.0 maturity models: Implications for small and medium-sized enterprises (SMEs),” Journal of Manufacturing Systems, vol. 49, pp. 194–214, 2018, doi: 10.1016/j.jmsy.2018.10.005.
17. J. Kusiak, “Fundamentals of smart manufacturing: Elements, processes, and systems,” International Journal of Production Research, vol. 57, no. 18, pp. 5608–5623, 2019, doi:
18. 10.1080/00207543.2018.1504241.
19. R. Tiwari and S. K. Singh, “Role of deep learning in robotics for smart manufacturing,” Procedia Computer Science, vol. 171, pp. 2258–2267, 2020, doi: 10.1016/j.procs.2020.04.244.
20. J. C. Chang, T. H. Wang, and S. Y. Wang, “Artificial intelligence and manufacturing industry development: A case study of China,” AI & Society, vol. 36, no. 4, pp. 869–884, 2021, doi: 10.1007/s00146-021-01150-9. Y. Lin, L. Zhou, and W. Xu, “Deep learning in manufacturing and its impact on industry practices,” Computers in Industry, vol. 138, Art. no. 103643, 2022, doi: 10.1016/j.compind.2022.103643.
21. A. Trivedi and S. B. Rane, “Adaptive robotics in manufacturing: Role of artificial intelligence in improving efficiency,” Procedia CIRP, vol. 106, pp. 250–255, 2022, doi: 10.1016/j.procir.2022.03.087.
22. N. Joshi and S. Maheshwari, “Artificial intelligence and cybersecurity challenges in Industry 4.0: A comprehensive review,” Computers & Security, vol. 114, Art. no. 102589, 2022, doi:
23. 10.1016/j.cose.2021.102589.
24. V. Pandey and M. Jha, “Intelligent manufacturing through AI-driven predictive maintenance systems,” Materials Today: Proceedings, vol. 47, pp. 5621–5625, 2021, doi: 10.1016/j.matpr.2021.05.515.
25. X. Zhang, M. Zhu, and S. Wang, “Application of self-trained AI systems in manufacturing: A review,” AI & Society, vol. 37, no. 1, pp. 95–109, 2022, doi: 10.1007/s00146-021-01159-y

OPEN ACCESS © CINEFORUM