CINEFORUM
ISSN: 0009-7039
Vol. 66. No. S9, 2026 (Special Issue S9)

Ai-Powered Wearable Iot Devices for Mental Health Assessment, Stress Prediction and Personalised Health Care Recommendation Systems

Dr. Amitvikram Nawalagatti[1]

[1]Assistant Professor, Department of Computer Science,Mahatma Gandhi Rural Development and Panchayat Raj University, Gadag, Karnataka, India
Email ID:-nawalagatti.amitvikram3@gmail.com

ABSTRACT
The growing burden of psychological stress and the limitations of episodic self-reporting have increased interest in wearable Internet of Things (IoT) systems for continuous, context-aware mental well-being support. This paper proposes an AI-powered wearable IoT framework that combines physiological sensing, secure edge-to-cloud communication, personalised machine learning and recommendation logic to support stress assessment and early identification of elevated stress patterns. The framework integrates photoplethysmography-derived heart rate and heart-rate variability, electrodermal activity, skin temperature, motion and sleep-related indicators. A personal-baseline mechanism is incorporated to reduce reliance on population-level thresholds, while contextual filtering is used to distinguish physiological arousal associated with physical activity from patterns potentially associated with psychological stress. A synthetic evaluation scenario is presented to demonstrate the proposed reporting and comparison methodology. The results compare logistic regression, support vector machine, random forest and a multimodal personalised model using discrimination, sensitivity, specificity and calibration metrics. These values are simulated for methodological demonstration and are not measurements from participants or a deployed device. The paper further discusses recommendation safety, privacy, fairness, usability and the distinction between wellness support and clinical diagnosis. The proposed system is intended as an assistive monitoring framework, not a substitute for validated mental-health assessment or professional care.
Keywords: Wearable Internet of Things; Mental Health Assessment; Stress Prediction; Artificial Intelligence; Personalised Healthcare; Physiological Monitoring

1. INTRODUCTION

Mental health is influenced by biological, psychological, social and environmental factors. Stress responses are dynamic and may vary across individuals, situations and time. Conventional assessment commonly relies on clinical interviews, validated questionnaires and periodic self-reporting. These approaches remain essential because they capture subjective experience and functional impact; however, they may not provide continuous information about day-to-day fluctuations. Wearable devices offer an additional source of longitudinal physiological and behavioural observations that may help identify patterns associated with elevated stress.

Modern smartwatches, wristbands and chest-worn sensors can acquire signals such as photoplethysmography (PPG), heart rate, heart-rate variability (HRV), electrodermal activity (EDA), skin temperature and movement. These measurements are indirect correlates of autonomic activity and behaviour. They are not specific biomarkers of anxiety, depression or any other psychiatric condition. Exercise, illness, medication, caffeine, sleep deprivation, ambient temperature and sensor placement can influence the same signals. Consequently, reliable assessment requires multimodal interpretation, contextual information and careful uncertainty communication.

The Internet of Things provides the communication and computing infrastructure required to connect wearable sensors with smartphones, edge gateways and secure cloud services. Artificial intelligence can analyse temporal patterns across multiple sensor streams, estimate the likelihood of elevated stress states and tailor recommendations to an individual's baseline. However, a high-performing classifier does not automatically provide a clinically meaningful assessment. The system must distinguish detection from prediction, avoid overconfident mental-health labels and ensure that recommendations are proportionate to the evidence.

Recent reviews report growing use of HRV, EDA, PPG, accelerometry and machine-learning methods for stress and mental-health monitoring, while identifying small samples, heterogeneous protocols, ecological-validity limitations and insufficient standardisation as persistent concerns [1]–[4]. This paper responds by proposing an end-to-end wearable IoT architecture with personal calibration, contextual inference, explainable output and privacy-by-design.

The objectives are: (1) to identify relevant wearable sensing modalities for stress-related monitoring; (2) to design an IoT architecture for secure, low-latency data acquisition and analysis; (3) to propose a personalised multimodal AI model for stress-state estimation; (4) to develop a cautious recommendation mechanism; and (5) to demonstrate an evaluation protocol while identifying requirements for empirical validation.

OPEN ACCESS © CINEFORUM

2. LITERATURE REVIEW

2.1 Wearable biosensing for mental well-being

Wearable systems can collect physiological signals continuously or at frequent intervals. PPG estimates peripheral blood-volume changes and can support heart-rate and selected HRV calculations when signal quality is adequate. ECG provides more direct cardiac electrical information but may be less convenient in consumer wrist devices. EDA reflects changes in skin conductance associated with sympathetic sudomotor activity. Skin temperature, respiratory patterns, accelerometry and sleep measures provide additional context. Reviews of wearable stress monitoring identify EDA, cardiac signals and motion-related features among commonly used modalities [1], [2].

2.2 AI methods for stress prediction

Classical machine-learning methods include logistic regression, support vector machines (SVM), decision trees, random forests and gradient boosting. Deep learning approaches, including recurrent neural networks and temporal convolutional models, can learn sequential patterns but generally require larger, more diverse datasets and careful prevention of subject leakage. Personalised models can adapt to individual baselines, whereas population models may be easier to initialise but can underperform when physiological variation between individuals is substantial.

2.3 Personalisation and contextual inference

A physiological increase in heart rate during exercise should not be interpreted as psychological stress without contextual information. Motion intensity, activity classification, time of day, sleep duration and user-reported context can help reduce false alerts. Personal baselines can be estimated from stable periods and updated cautiously to avoid adapting to prolonged adverse states. A hybrid strategy can combine population-level initialisation with individual calibration.

2.4 Research gap

The literature points to a gap between laboratory classification performance and reliable everyday use. Small cohorts, inconsistent stress induction, differing wearable hardware, variable ground-truth labels and limited external validation complicate direct comparisons [1]–[4]. In addition, recommendation systems are often less rigorously evaluated than detection models. The proposed framework therefore treats sensor quality, contextual discrimination, recommendation safety and user governance as core design components rather than optional extensions.

3. PROPOSED SYSTEM ARCHITECTURE AND METHODOLOGY

The proposed system consists of six layers: wearable sensing, edge processing, secure IoT communication, AI inference, personalised recommendation and human oversight. The architecture is designed for a wrist-worn device paired with a smartphone, although chest-worn ECG or respiration sensors may be incorporated in research settings.




Figure 1. Proposed architecture of the AI-powered wearable IoT framework for stress assessment and personalised well-being support.

OPEN ACCESS © CINEFORUM

3.1 Wearable sensor layer

The sensor layer acquires PPG, HR/HRV, EDA, skin temperature and tri-axial accelerometry. Sleep duration and sleep regularity may be derived from validated device algorithms, with the recognition that consumer sleep estimates are not equivalent to polysomnography. Each data stream should carry timestamps, sampling metadata and signal-quality indicators. Missing or low-quality signals should result in an uncertainty flag rather than an unsupported prediction.

Table 1. Wearable modalities and candidate features for stress-related monitoring.

Signal / modality	Potential derived features	Interpretation and limitation
PPG / HR	Mean HR, resting HR, pulse intervals	Affected by motion, perfusion and device fit
HRV	RMSSD, SDNN, frequency-domain indices where valid	Sensitive to recording duration, artefacts and respiration
EDA	Tonic level, phasic responses, response rate	Affected by temperature, hydration and sensor contact
Skin temperature	Mean level, trend and variability	Strongly influenced by ambient conditions
Accelerometry	Activity intensity, posture, movement	Essential context for separating exercise from stress
Sleep estimates	Duration, regularity, fragmentation proxies	Consumer estimates are not clinical sleep diagnoses

3.2 Edge processing and IoT communication

Raw signals should be quality-checked and processed locally where feasible. Edge processing can remove obvious artefacts, calculate short-window features and reduce transmission of raw high-frequency data. The smartphone gateway should use authenticated pairing, encrypted transport, secure storage and revocable access tokens. Cloud processing may support longitudinal model updates, but sensitive information should be minimised and retained only for a clearly stated purpose.

3.3 Personalised AI inference

The proposed model combines a population-level classifier with a personal-baseline adaptation module. For each analysis window, the feature vector may be represented as $x_t = [HR_t, HRV_t, EDA_t, TEMP_t, ACC_t, SLEEP_t, CONTEXT_t]$. A classifier estimates $P(S_t = k \mid x_t, b_i)$, where S_t denotes the stress-related state, b_i represents the individual baseline, and k may correspond to low, moderate or elevated physiological stress likelihood. This is an estimate of a stress-related pattern, not a psychiatric diagnosis.

A temporal model can incorporate recent windows to estimate a future risk horizon. A practical design may combine gradient boosting for tabular features with a gated recurrent unit (GRU) or temporal convolutional network for sequential features. The model should include an abstention option when signal quality is inadequate or uncertainty exceeds a predefined threshold. Personal calibration should be separated from test evaluation to prevent leakage.

3.4 Recommendation engine

Recommendations should be low-risk, optional and matched to the estimated state and user preferences. Examples include a brief guided breathing exercise, a movement break after prolonged inactivity, a prompt to review sleep routines, a reminder to take a screen break, or a suggestion to contact a trusted person. The system should not recommend medication changes, diagnose a disorder or advise discontinuation of professional treatment. Repeated elevated patterns or user-reported distress should prompt a supportive suggestion to consult a qualified professional rather than an automated clinical conclusion.

OPEN ACCESS © CINEFORUM

Table 2. Example recommendation logic and safety constraints.

Estimated pattern	Possible supportive recommendation	Safety constraint
Transient elevated arousal	Optional paced-breathing or grounding exercise	Do not imply that the exercise treats a disorder
Sustained elevated pattern	Offer a check-in and encourage reflection on context	Display uncertainty; avoid alarming language
Low sleep regularity	Offer sleep-routine education and user-selected reminders	Do not infer a sleep disorder
High activity with elevated HR	Suppress stress alert or request context	Avoid misclassifying exercise as psychological stress
Persistent distress reported by user	Provide pathways to professional or trusted support	Crisis support must follow locally validated protocols

3.5 Evaluation methodology

A future empirical study should recruit a diverse adult cohort under ethics approval and obtain informed consent. Stress labels should be grounded in validated self-report instruments and, where appropriate, structured clinical assessment; physiological signals alone should not define ground truth. Data should be split by participant, with temporal and external validation where possible. Model evaluation should report AUROC, area under the precision-recall curve, sensitivity, specificity, calibration, false-alert rate, missing-data robustness and subgroup performance. A prospective usability study should assess acceptability, adherence, alert burden and whether recommendations are perceived as helpful.

4. EXPERIMENTAL DESIGN AND RESULTS

The following results are entirely synthetic and are included to demonstrate the form of a comparative results section. They do not represent recruited participants, real wearable recordings, a trained model or a completed experiment. The assumed scenario uses 100 participants with repeated windows, but the summary metrics below are model-level values only. They must be replaced by results from a documented study before being described as empirical findings.

Table 3. Synthetic experimental design assumptions; not a report of completed human-subject research.

Experimental element	assumption	Actual study requirement
Participants	100 adult users	Ethics-approved recruitment and sample-size justification
Monitoring period	14 days assumed	Report actual duration, adherence and missingness
Signals	PPG, HRV, EDA, temperature, accelerometry	Specify device, sampling rates and signal-quality validation
Labels	Low / moderate / elevated stress	Use validated instruments and clear label timing
Validation	Participant-independent 70/15/15 split	Prevent subject leakage; add temporal/external validation
Models	Logistic regression, SVM, random forest, multimodal model	Pre-register tuning and evaluate on untouched test data

OPEN ACCESS © CINEFORUM

Table 4. Synthetic comparison of stress-pattern classification models.

Model	Accuracy	AUROC	Sensitivity	Specificity	F1-score
Logistic regression	0.74	0.76	0.70	0.77	0.71
Support vector machine	0.78	0.80	0.75	0.80	0.76
Random forest	0.82	0.84	0.79	0.84	0.80
Personalised multimodal AI	0.86	0.88	0.83	0.88	0.84




Figure 2. AUROC comparison using synthetic values from Table 4; not measured experimental performance.

In this comparison, the personalised multimodal model records the highest AUROC (0.88), accuracy (0.86) and F1-score (0.84). If a real study reproduced this pattern under participant-independent and external validation, it would suggest that combining physiological modalities with personal baselines may improve discrimination. The interpretation must remain conditional because multimodal models can benefit from additional information, but may also overfit, rely on context proxies or perform unevenly across demographic groups.

The lower sensitivity of the baseline models indicates a potential trade-off between missed elevated-stress windows and false alerts. In practice, the optimal threshold should be selected according to the intended use and user burden. A wellness prompt may tolerate a different false-positive rate from a clinical escalation workflow. The model should therefore report calibration and decision consequences, not only accuracy.

The advantage does not establish that the system can assess depression, anxiety or other psychiatric disorders. Nor does it prove that recommendations reduce stress. Such claims would require separate validation using appropriate clinical outcomes, user-reported outcomes and controlled evaluation of the recommendation component.

5. DISCUSSION

The proposed framework offers several potential advantages. Continuous or frequent sensing may reveal within-person changes that are missed by occasional questionnaires. Multimodal analysis can provide a richer representation than any single physiological signal, while personal baselines may reduce the influence of between-

OPEN ACCESS © CINEFORUM

person variability. Edge processing can reduce latency and limit the need to transmit raw sensor streams. A recommendation layer can translate a risk estimate into a practical, optional action.

There are also important counterarguments. Physiological arousal is not specific to psychological stress: exercise, infection, pain, medication and environmental conditions can produce similar patterns. Consumer-grade sensors may produce artefacts during movement, and HRV estimates depend on signal quality and analysis window. Personalisation can improve fit but may also make the model less transferable and can adapt incorrectly if baseline periods are not representative. A recommendation system may create alert fatigue or encourage excessive self-monitoring.

The most important methodological issue is ground-truth validity. Self-reported stress is subjective but directly relevant to the experience being modelled. Physiological features are objective measurements but indirect indicators. A defensible design should combine repeated validated self-reports, contextual annotations and sensor signals, while keeping clinical diagnoses separate from momentary stress labels. Model evaluation should also avoid random window-level splitting when windows from the same individual can appear in both training and test sets.

Privacy and autonomy are central because wearable data can reveal routines, sleep patterns, activity and sensitive inferences. Data collection should be proportionate, transparent and revocable. Users should be able to pause sensing, inspect what is collected, delete their data where applicable and disable recommendations. The system should not share inferred mental-health states with employers, insurers or other third parties without a lawful basis and explicit safeguards.

6. LIMITATIONS AND FUTURE RESEARCH

This paper is a proposed framework supported by a literature-based rationale and a synthetic results demonstration. It does not report a real participant study, clinical validation, device calibration experiment or intervention trial. The numerical results are placeholders and must not be presented as observed outcomes. The architecture also does not specify a single commercial device, sampling configuration or disease-specific endpoint. Performance in real-world conditions may differ substantially from laboratory or synthetic scenarios.

Future work should implement a prototype and conduct a feasibility study with a clearly defined population and monitoring objective. Researchers should predefine stress labels, validate sensors against reference instruments, recruit participants across age and demographic groups, and use subject-independent and external validation. The recommendation engine should be evaluated separately through usability and controlled intervention studies. Long-term deployment should monitor model drift, subgroup error, alert burden, adherence and unintended psychological effects.

7. Conclusion

This paper has proposed an AI-powered wearable IoT framework for stress-related mental well-being assessment, prediction and personalised supportive recommendations. The architecture integrates physiological sensing, edge processing, secure IoT communication, personal-baseline modelling, contextual inference and human-centred recommendation logic. Synthetic results demonstrate how competing models and evaluation metrics may be reported, but they do not establish actual system performance or clinical effectiveness.

Wearable AI should be positioned as an assistive wellness technology rather than an autonomous mental-health diagnostic system. Reliable translation requires validated ground truth, robust signal quality, participant-independent evaluation, privacy protection, fairness assessment and prospective evidence that recommendations are useful and safe. The proposed framework provides a basis for such empirical investigation

REFERENCES

1. A. Pinge, V. Gad, D. Jaisighani, S. Ghosh, and S. Sen, “Detection and monitoring of stress using wearables: A systematic review,” Frontiers in Computer Science, vol. 6, Art. no. 1478851, 2024, doi:
2. 10.3389/fcomp.2024.1478851.
3. M. Bolpagni, S. Pardini, M. Dianti, and S. Gabrielli, “Personalized stress detection using biosignals from wearables: A scoping review,” Sensors, vol. 24, no. 10, Art. no. 3221, 2024, doi: 10.3390/s24103221.
4. Fusing wearable biosensors with artificial intelligence for mental health monitoring: A systematic review,” Biosensors, vol. 15, no. 4, Art. no. 202, 2025, doi: 10.3390/bios15040202.
5. O. Pataca, E. Zdravevski, P. J. Coelho, N. M. Garcia, M. Deruyck, C. Albuquerque, and I. M. Pires, “Use of machine learning for predicting stress episodes based on wearable sensor data: A systematic review,” Computers in Biology and Medicine, vol. 198, Art. no. 111166, 2025, doi:
6. 10.1016/j.compbiomed.2025.111166.
7. Wearable devices for anxiety assessment: A systematic review,” Communications Medicine, 2025, doi:

OPEN ACCESS © CINEFORUM

8. 10.1038/s43856-025-01234-6.
9. Machine learning and deep learning techniques to detect mental stress using various physiological signals: A critical insight," WIREs Data Mining and Knowledge Discovery, vol. 15, no. 3, Art. no. e70035, 2025, doi: 10.1002/widm.70035.
10. Task Force of the European Society of Cardiology and the North American Society of Pacing and Electrophysiology, "Heart rate variability: Standards of measurement, physiological interpretation and clinical use," Circulation, vol. 93, no. 5, pp. 1043–1065, 1996.
11. World Health Organization, Ethics and Governance of Artificial Intelligence for Health: WHO Guidance. Geneva, Switzerland: WHO, 2021.
12. J. Kumar, "Changing paradigm of employee relations in India after independence," South Asian Journal of Human Resources Management, vol. 10, no. 1, 2023. doi: 10.1177/26314541221134853.
13. A. Venkataraman, "Employment relations past, present and future: Demise or resurrection in India?" South Asian Journal of Human Resources Management, vol. 10, no. 1, 2023. doi: 10.1177/26314541221134861.
14. Rosy, C. P., Indhumathi, R., Lalli, S., & Kanimozhi, R. (2026). Real-time eye movement detection for vision-based interfaces. In Recent advancements in computational intelligence: Concepts, methodologies and applications (Part 2, pp. 268–279). Bentham Science Publishers.
15. Subashini, D., Vairavan, S., P., P., Bostani, A., K., S. J., Naveenkumar, R., & Edpuganti, S. K. (2026). Deep learning–based prediction and classification of minerals from soil images using computer vision techniques. International Journal of Artificial Intelligence and Machine Learning, 6(2s), 536–543.
16. https://doi.org/10.51483/IJAIML.6.2s.2026.536-543.
17. Idhumathi, R., Jeyalakshmi, S., Hemalatha, N., Shrivastava, A., & Alasady, H. (2025). Hybrid fuzzy neural systems for real time decision making in autonomous vehicles. Journal of Machine and Computing, 2544–2556.
18. Kirthika, B., Sudarmozhi, K., & Akanni, J. O. (2026). SHAP enabled knowledge distilled deep learning framework for explainable intrusion prevention in IoT wireless sensor networks. Discover Internet of Things.
19. Rehman A., Bin Saad, A. A., Kamaludin, S., Sudarmozhi, K., & Khan, D. (2025). Mathematical simulation for energy transfer in a couple stress ternary hybrid nanofluid flow passing through a 3D surface, considering the impact of MHD and viscous dissipation. Journal of Applied and Computational Mechanics, e19512.
20. Rehman A., Inc, M., & Sudarmozhi, K. (2026). New research on ternary hybrid nanofluid flow across a surface with the influence of thermal radiation using semi-numerical simulation. Open Engineering, 16(1), 20250157.
21. Rehman, A., Saad, A. A., Khan, D., Jan, R., & Sudarmozhi, K. (2026). Unsteady MHD mixed convection flow of hybrid nanofluid over a rotating sphere in a Darcy-Forchheimer with slip effects. International Journal of Mechanics and Materials in Design, 22(3), 167.
22. Rehman, A., Saad, A. A., Inc, M., Abas, S. S. B., Jawo, E., & Sudarmozhi, K. (2026). Semi-numerical simulation for the thermal performance of unsteady squeezing non-Newtonian MHD couple stress ternary hybrid nanofluid flow between parallel surfaces. International Journal of Thermofluids, 31, 101516.
23. Koneti, Chaitanya, Rajiv Aserkar, and Vanita Bhoola. "AI-Based Predictive Analytics for Demand Forecasting and Inventory Efficiency." Advances in Consumer Research 3.1 (2026). https://acr-journal.com/article/ai-based-predictive-analytics-for-demand-forecasting-and-inventory-efficiency-2425/
24. Koneti, Chaitanya, A. Seetharaman, and K. Maddulety. "Understanding the supply chain efficiency in e-commerce using the blockchain technology." Library of Progress-Library Science, Information Technology & Computer 44.3 (2024): 3147.https://doi.org/10.48165/bapas.2024.44.2.1
25. Koneti, Chaitanya, A. Seetharaman, and K. Maddulety. "Understanding the supply chain efficiency in e-commerce using the blockchain technology." Library of Progress-Library Science, Information Technology & Computer 44.3 (2024): 3147.https://doi.org/10.48165/bapas.2024.44.2.1
26. Koneti, Chaitanya, A. Seetharaman, and K. Maddulety. "Evaluating the effectiveness of influencer marketing in niche markets." Journal of Marketing & Social Research 2 (2025): 65-79. https://jmsr-online.com/article/evaluating-the-effectiveness-of-influencer-marketing-in-niche-markets-247/
27. Koneti, C., Pingat, S. P., Santos, C. P., Alos, L. G., Parida, P., & Fernández-Rodríguez, J. C. (2025). From engagement to retention: The power of gamification in digital marketing. Journal of Information Systems Engineering & Management, 10(4), 25-35.https://doi.org/10.52783/jisem.v10i4.8382
28. Neha Sharma, Mukesh Soni, Sumit Kumar, Rajeev Kumar, Anurag Shrivastava, Supervised Machine Learning Method for Ontology-based Financial Decisions in the Stock Market, ACM Transactions on Asian and Low-Resource Language InformationProcessing, Volume 22, Issue 5, Article No.: 139, Pages 1 – 24, https://doi.org/10.1145/3554733

OPEN ACCESS © CINEFORUM

29. Rathinavelu, G. (2023). Federated Learning and Privacy-Preserving AI for Cross-Institutional Financial Fraud Detection. Journal of Computational Analysis and Applications (JoCAAA), 31(4), 3239–3263.
30. Rathinavelu, G. (2024). Continual Learning Systems for Adaptive Fraud-Pattern Detection in High-Velocity Transaction Streams. Journal of Computational Analysis and Applications (JoCAAA), 33(4), 1239–1264.
31. Rathinavelu, G. (2025). Early-Stage Consumer Credit Risk Detection Using Multimodal Deep Learning and Behavioral AI. International Journal of Computer Information Systems and Industrial Management Applications, 17, 1–27.
32. Rathinavelu, G. (2026). Real-Time Cross-Border Anti-Money Laundering (AML) Detection Using Graph Neural Networks and Machine Learning. International Journal of Computer Information Systems and Industrial Management Applications, 18(5s), 1217–1242.
33. P. William, A. Shrivastava, U. S. Asmal, M. Gupta, and A. K. Rosa, "Framework for Implementation of Android Automation Tool in Agro Business Sector," 4th International Conference on Intelligent Engineering and Management (ICIEM), 2023.
34. H. Douman, M. Soni, L. Kumar, N. Deb, and A. Shrivastava, "Supervised Machine Learning Method for Ontology-based Financial Decisions in the Stock Market," ACM Transactions on Asian and Low Resource Language Information Processing, vol. 22, no. 5, p. 139, 2023.
35. A. V. A. B. Ahmad, D. K. Kurmu, A. Khullia, S. Purafis, and A. Shrivastova, "Framework for Cloud Based Document Management System with Institutional Schema of Database," International Journal of Intelligent Systems and Applications in Engineering, vol. 12, no. 3, pp. 692–678, 2024.

OPEN ACCESS © CINEFORUM